

Parameters- Signlightsled™ Generation 1
Specifications

Model Number`	Tube	Wattage	Lumens	Cover
SL07T10600450	F-18	7 W	910 lm	Clear
SL13T10600600	F-24	13W	1560 lm	Clear
SL13T10600750	F-30	13 W	1690 lm	Clear
SL13T10600900	F-36	16W	2080 lm	Clear
SL16T10601050	F-42	21 W	2700 lm	Clear
SL21T10601200	F-48	21W	2730 lm	Clear
SL28T10601500	F-60	28W	3640 lm	Clear
SL28T10601600	F-64	28W	3640 lm	Clear
SL38T10601800	F-72	38W	4750 lm	Clear
SL38T10602100	F-84	38W	4750 lm	Clear
SL51T10602475	F-96	51W	6630 lm	Clear
SL51T10602700	F-108	51W	6630 lm	Clear
SL60T10602925	F-117	60W	8450 lm	Clear
SL60T10603000	F-120	60 W	8450 lm	Clear

INPUT VOLTAGE AC100-270V

IP RATING 65 CONNECTIONS

OPERATING TEMPERATURES -20° TO 45° C

UL CERTIFIED

TUBES ARE PERFECTY CORRELATED WITH FLUORESCENT TUBES TO PROVIDE
HASSLE-FREE INSTALLATION.



www.Signlightleds.com

Info@signlightleds.com

PO Box 924 Granite Falls, NC 28630

828-455-1787