

Parameters- Signlightsled™ Generation 2
Specifications

| Model Number` | Tube | Wattage | Lumens | Cover |
|-----------------|-------|---------|---------|-------|
| 2SL07T10600450 | F-18 | 7 W | 910 lm | Clear |
| 2SL13T10600600 | F-24 | 13W | 1560 lm | Clear |
| 2SL13T10600750 | F-30 | 13 W | 1690 lm | Clear |
| 2SL13T10600900 | F-36 | 16W | 2080 lm | Clear |
| 2SL16T10601050 | F-42 | 21 W | 2700 lm | Clear |
| 2SL21T10601200 | F-48 | 21W | 2730 lm | Clear |
| 2SL28T10601500 | F-60 | 28W | 3640 lm | Clear |
| 2SL28T10601600 | F-64 | 28W | 3640 lm | Clear |
| 2SL38T10601800 | F-72 | 38W | 4750 lm | Clear |
| 2SL38T10602100 | F-84 | 38W | 4750 lm | Clear |
| 2SL51T10602475 | F-96 | 51W | 6630 lm | Clear |
| 2SL51T10602700* | F-108 | 51W | 6630 lm | Clear |
| 2SL60T10602925* | F-117 | 60W | 8450 lm | Clear |
| 2SL60T10603000* | F-120 | 60 W | 8450 lm | Clear |
| | | | | |

- F-108, F-117, and F-120 are 2 pieces that connect to form tube- this design allows for easier transportation and handling.

INPUT VOLTAGE AC100-270V

IP RATING 65 CONNECTIONS

OPERATING TEMPERATURES -20° TO 45° C

UL CERTIFIED

TUBES ARE PERFECTY CORRELATED WITH FLUORESCENT TUBES TO PROVIDE
HASSLE-FREE INSTALLATION.



www.Signlightleds.com

Info@signlightleds.com

PO Box 924 Granite Falls, NC 28630

828-455-1787